MLR5000

- Label holder with customizable backlit LED
- LED for handle and temperature status
- No key override
- TCP/IP Ethernet
- 125kHz HID Prox
- 13.56MHz HID iClass, Mifare Classic, Mifare DESFire EV1, Mifare DESFire EV2
- Storage capacity for 2,000 cards and pins
- Storage capacity for 500 events (offline) and 30 time profiles
- PoE IEEE 802.3af (Power over Ethernet) capable

Dimension



MLR5000

Technical Details

- Power Supply: 12 V ± 10% (DC)
- Bias-Current: 40mA (DC)
- Max Current: 440mA (DC)
- Temperature range: -20C to + 70C
- Sheet metal thickness from 1.5-2mm (plus powder coating)
- Top mounting screws Tq to 1.0-1.2Nm
- Bottom cap screws Tq to 0.4Nm

Connection

MLR5000

LED Status

MLR5000

Item number

MLR5000 (125 kHz) for Offset
610-9607.00-00000

MLR5000 (125 kHz) for Rod Latch
610-9601.00-00000

MLR5000 (125 kHz) for Cam Latch
610-9639.00-00000

MLR5000 (125 kHz) for Rod Latch (Rittal)
610-9645.00-00000

MLR5000 (13.56 MHz) for Offset
610-9607.00-11356

MLR5000 (13.56 MHz) for Rod Latch
610-9601.00-11356

MLR5000 (13.56 MHz) for Cam Latch
610-9639.00-11356

MLR5000 (13.56 MHz) for Rod Latch (Rittal)
610-9645.00-11356

Delivery

Swinghandle

Additional products

Door contact

Power supply (12/24 V DC)